

## Conti Coach HA3 (with Active Sensor) All-Position Long Haul Coach

Applications: Long haul, over the highway steering and all-position use, for coach and large RV use.








## **Conti Coach HA3 (with Active Sensor)**

**All-Position Long Haul Coach** 



STATIC LOADED

501



ARTICLE

NUMBER

05651710000

LOAD RANGE



OVERALL INFLATED

DIAMETER

424 1077



INFLATED

124



SECTION

136 345



APPROVED

RIM(S)

9.00, 8.25

MINIMUM DUAL

13.8 351 488 303

**PER UNIT** 





(4125, 900)

315

Note - Rim listed first is the measuring rim. Minimum Dual Spacing calculated without chains. These specifications subject to change without notice. recommended nor endorsed. Overall widths will change 01 inch (25 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly, 315/80R225 tires used on 8.25 rims are restricted to a maximum of 7610 lbs at 120 psi. Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer



TIRE SIZE

315/80R22.5 \*

Extra load-carrying capacity with a specially reinforced Stable Bead Technology.



TREAD

DEPTH (32nds)

17

MAX

SPEED

Durable casing for premium retreadability and enhanced mileage.



Noise-Reducing Tread Design for serene and comfortable travel.




traction with interlocking 3D sipes.



Embedded with TPMS Active Sensor Technology.

## Intelligent Tire | Equipped with TPMS Sensor

- Accurate, real-time tire pressure and temperature readings
- Sensor lasts 6 years / 400,000 miles to minimize disruptions
- Sensor provides true casing temperature allowing preventive actions that make your tire last longer
- Avoids valve damage and air leaks by mounting on the inner liner



**Applications:** Long haul, over the highway steering and all-position use, for coach and large RV use.