

Conti HAU 3 WT (Rename of Conti CityService HA3)

Urban All-Position for Waste Transport

Applications: Waste transportation and other high scrub, urban applications.



Conti HAU 3 WT (Rename of Conti CityService HA3)

Urban All-Position for Waste Transport

GOODS PEOPLE CONSTRUCTION



PRODUCT DATA




	TIRE SIZE	LOAD RANGE	ARTICLE NUMBER (Conti HSL 3)	TREAD DEPTH (32nds)	MAX SPEED (MPH)	STATIC LOADED RADIUS		OVERALL INFLATED DIAMETER		OVERALL INFLATED WIDTH		LOADED SECTION WIDTH		APPROVED RIM(S)	MINIMUM DUAL SPACING		REVS PER UNIT		TIRE WEIGHT		MAX. LOAD @ INFLATION	
						IN	MM	IN	MM	IN	MM	IN	MM		IN	MM	MI	KM	LB	KG	SINGLE	DUAL
						LBS, PSI (KG, KPa)		LBS, PSI (KG, KPa)														
CityService HA3	315/80R22.5*	L	05140590000	26	68	20.0	507	431	1095	12.4	314	13.8	349	9.00, 8.25	13.8	351	480	298	163	74	10000, 130 (4540, 900)	9090, 130 (4125, 900)
Conti HAU 3 WT	315/80R22.5*	L	05141090000	26	68	20.0	507	431	1095	12.4	314	13.8	349	9.00, 8.25	13.8	351	480	298	163	74	10000, 130 (4540, 900)	9090, 130 (4125, 900)

TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS

Note - Rim listed first is the measuring rim. Minimum Dual Spacing calculated without chains. * - ECE Certified. # - Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. 315/80R22.5 tires used on 8.25" rims are restricted to a maximum of 7610 lbs at 120 psi. Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.



Four rib tread pattern with zigzag groove geometry for resistance to high scrub applications.



Innovative tread compound for outstanding mileage and heat reduction.



Improved bead design for increased durability and resistance to brake heat.



Extra sidewall protection for better resistance to curbs, cuts, and other sidewall abrasions.

Applications: Waste transportation and other high scrub, urban applications.