

# Conti Hybrid HD3 Super Regional Drive

Applications: Combined long haul highway and regional tandem drive position.



Legend:

3G Casing	SmartWay Verified	With TPMS Sensor	Retread Available
-----------	-------------------	------------------	-------------------

# Conti Hybrid HD3

## Super Regional Drive

GOODS  PEOPLE  CONSTRUCTION




### PRODUCT DATA



TIRE SIZE	LOAD RANGE	ARTICLE NUMBER	TREAD DEPTH (32nds)	MAX SPEED (MPH)	STATIC LOADED RADIUS		OVERALL INFLATED DIAMETER		OVERALL INFLATED WIDTH		LOADED SECTION WIDTH		APPROVED RIM(S)	MINIMUM DUAL SPACING		REVS PER UNIT		TIRE WEIGHT		MAX. LOAD @ INFLATION	
					IN	MM	IN	MM	IN	MM	IN	MM		IN	MM	MI	KM	LB	KG	SINGLE	DUAL
					LBS, PSI (KG, KPa)		LBS, PSI (KG, KPa)														
11R22.5	G	05210150000	27	75	19.7	500	42.0	1067	11.7	296	13.1	331	8.25, 750	12.5	318	493	306	130	59	6175, 105 (2800, 720)	5840, 105 (2650, 720)
11R22.5	H	05210160000	27	75	19.7	500	42.0	1067	11.7	296	13.1	331	8.25, 750	12.5	318	493	306	131	60	6610, 120 (3000, 830)	6005, 120 (2725, 830)
295/75R22.5	G	05210170000	27	75	19.1	484	40.6	1031	11.7	296	12.7	323	8.25, 900	12.5	318	510	317	125	57	6175, 110 (2800, 760)	5675, 110 (2575, 760)
11R24.5	H	05210560000	27	75	20.6	522	43.9	1114	11.6	294	13.0	330	8.25, 750	12.5	318	472	293	146	67	7160, 120 (3250, 830)	6610, 120 (3000, 830)
275/70R22.5* (Tread B)	H	05210920000	22	81	17.6	447	38.3	974	10.9	276	11.3	287	8.25, 750	12.1	307	551	342	115	52	6940, 130 (3150, 900)	6395, 130 (2900, 900)

TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS

Note - Rim listed first is the measuring rim. Minimum Dual Spacing calculated without chains. \* - ECE Certified # - Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change .01 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.



**Fuel efficient tread compound** delivers exceptional rolling resistance balanced with mileage.



**Directional tread design** with regenerating sipe technologies deliver outstanding traction in tandem axle fitment.



Optimized contour and **balanced footprint distribution** provide extended tread life and premium wear performance.



Built on the **Conti 3G Casing** for maximum retreadability.

**Applications:** Combined long haul highway and regional tandem drive position.