

Conti HSR 3 Regional All-Position

Applications: Regional hauling and on/off road, all-position.





Straight4ward
New Nomenclature Product Name Change


Legend:

3G Casing	SmartWay Verified	With TPMS Sensor	Retread Available
-----------	-------------------	------------------	-------------------

Conti HSR 3

Regional All-Position

GOODS PEOPLE CONSTRUCTION




PRODUCT DATA



TIRE SIZE	LOAD RANGE	ARTICLE NUMBER	TREAD DEPTH (32nds)	MAX SPEED (MPH)	STATIC LOADED RADIUS		OVERALL INFLATED DIAMETER		OVERALL INFLATED WIDTH		LOADED SECTION WIDTH		APPROVED RIM(S)	MINIMUM DUAL SPACING		REVS PER UNIT		TIRE WEIGHT		MAX. LOAD @ INFLATION	
					IN	MM	IN	MM	IN	MM	IN	MM		IN	MM	MI	KM	LB	KG	LBS, PSI (KG, KPa)	LBS, PSI (KG, KPa)
11R22.5	G	05124370000	23	75	19.5	495	41.9	1064	11.6	295	13.0	330	8.25, 750	12.5	318	494	307	131	59	6175, 105 (2800, 720)	5840, 105 (2650, 720)
11R22.5	H	05124380000	23	75	19.5	495	41.9	1064	11.6	295	13.0	330	8.25, 750	12.5	318	494	307	133	61	6610, 120 (3000, 830)	6005, 120 (2725, 830)
12R22.5	H	05124390000	23	75	20.2	513	42.8	1086	11.9	302	13.1	333	9.00, 8.25	13.7	348	484	301	144	65	7390, 120 (3350, 830)	6780, 120 (3075, 830)
295/75R22.5	G	05124400000	23	75	18.9	480	40.2	1022	11.8	299	12.9	328	8.25, 750	13.4	340	514	320	121	55	6175, 110 (2800, 760)	5675, 110 (2575, 760)
295/75R22.5	H	05124410000	23	75	18.9	480	40.2	1022	11.8	299	12.9	328	8.25, 750	13.4	340	514	320	126	57	7160, 120 (3250, 830)	6610, 120 (3000, 830)
11R24.5	H	05124430000	23	75	20.5	521	43.8	1113	11.6	295	13.0	330	8.25, 750	12.5	318	473	294	143	65	7160, 120 (3250, 830)	6610, 120 (3000, 830)
285/75R24.5	H	05124450000	23	75	19.5	496	41.6	1057	11.8	300	12.9	328	8.25	12.5	318	498	309	134	61	6780, 120 (3075, 830)	6175, 120 (2800, 830)

TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS

Note - Rim listed first is the measuring rim. Minimum Dual Spacing calculated without chains. # - Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.



Rigid belt package with full width top belt and extra sidewall protection for increased durability.



Zigzag center groove geometry increases the number of biting edges for increased traction.



Pyramidal stone ejection system for maximum casing protection.



Built on the innovative **Conti 3G Casing** for maximum retreadability.



Mileage Improvement vs. HSR2

*Based on projected calculations.

Applications: Regional hauling and on/off road, all-position.