

HDC1 Construction Drive

Applications: Construction, coal haulers, logging, waste haulers and other on/off highway service.



Legend:

3G Casing	SmartWay Verified	With TPMS Sensor	Retread Available
-----------	-------------------	------------------	-------------------

HDC1

Construction Drive

GOODS PEOPLE CONSTRUCTION



PRODUCT DATA



TIRE SIZE	LOAD RANGE	ARTICLE NUMBER	TREAD DEPTH (32nds)	MAX SPEED (MPH)	STATIC LOADED RADIUS		OVERALL INFLATED DIAMETER		OVERALL INFLATED WIDTH		LOADED SECTION WIDTH		APPROVED RIM(S)	MINIMUM DUAL SPACING		REVS PER UNIT		TIRE WEIGHT		MAX. LOAD @ INFLATION	
					IN	MM	IN	MM	IN	MM	IN	MM		IN	MM	MI	KM	LB	KG	SINGLE	DUAL
					LBS, PSI (KG, KPa)		LBS, PSI (KG, KPa)														
11R22.5	H	05687040000	32	68	19.7	500	42.4	1077	11.1	282	12.2	310	8.25, 7.50	12.5	318	488	303	130	59	6610, 120 (3000, 830)	6005, 120 (2725, 830)
11R24.5	H	05687050000	32	68	20.7	526	44.4	1128	11.1	282	12.2	310	8.25, 7.50	12.5	318	466	290	139	63	7160, 120 (3250, 830)	6610, 120 (3000, 830)

TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS

Note - Rim listed first is the measuring rim. Minimum Dual Spacing calculated without chains. * - ECE Certified # - Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change 01 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.



32/32" tread pattern and compound integrated for superior original mileage and traction.



Optimized contour ensures higher load reserves and less deformation.



Patented tread pattern and contour provide stable casing value through reduced stone retention and improved impact resistance.

Applications: Construction, coal haulers, logging, waste haulers and other on/off highway service.