

HDL2 DL

Long Haul Drive, Deep Lug

Applications: Long haul, over the highway drive position.



Legend:

3G Casing	SmartWay Verified	With TPMS Sensor	Retread Available
-----------	-------------------	------------------	-------------------

HDL2 DL

Long Haul Drive, Deep Lug

GOODS PEOPLE CONSTRUCTION



PRODUCT DATA



TIRE SIZE	LOAD RANGE	ARTICLE NUMBER	TREAD DEPTH (32nds)	MAX SPEED (MPH)	STATIC LOADED RADIUS		OVERALL INFLATED DIAMETER		OVERALL INFLATED WIDTH		LOADED SECTION WIDTH		APPROVED RIMS	MINIMUM DUAL SPACING		REVS PER UNIT		TIRE WEIGHT		MAX. LOAD @ INFLATION	
					IN	MM	IN	MM	IN	MM	IN	MM		IN	MM	MI	KM	LB	KG	SINGLE	DUAL
					LBS, PSI (KG, KPa)		LBS, PSI (KG, KPa)														
11R22.5*	G	05686240000	32	75	19.7	501	42.2	1071	11.6	294	13.0	329	8.25, 750	12.5	318	491	305	138	63	6175, 105 (2800, 720)	5840, 105 (2650, 720)
11R22.5*	H	05687030000	32	75	19.7	501	42.2	1071	11.6	294	13.0	329	8.25, 750	12.5	318	491	305	139	63	6610, 120 (3000, 830)	6005, 120 (2725, 830)
275/80R22.5*	G	05686270000	32	75	19.1	485	40.8	1036	11.4	289	12.7	323	8.25, 750	12.5	318	507	315	133	60	6175, 110 (2800, 760)	5675, 110 (2575, 760)
11R24.5*	G	05686250000	32	75	20.7	526	44.2	1122	11.6	295	13.0	330	8.25, 750	12.5	318	468	291	148	67	6610, 105 (3000, 830)	6005, 105 (2725, 720)
11R24.5*	H	05686260000	32	75	20.7	526	44.2	1122	11.6	295	13.0	330	8.25, 750	12.5	318	468	291	149	68	7160, 120 (3250, 830)	6610, 120 (3000, 830)
285/75R24.5*	G	05686280000	32	75	19.7	501	42.2	1073	11.4	290	12.6	321	8.25	12.5	318	490	305	136	62	6175, 110 (2800, 760)	5675, 110 (2575, 760)

TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS

Note - Rim listed first is the measuring rim. * - ECE Certified Minimum Dual Spacing calculated without chains. # - Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.



32/32" tread depth provides high mileage and low cost per mile.



Patented innovative groove technology leads to minimal stone retention, extending casing life.



Minimized wear and excellent traction over the life of the tire, through a **wide, closed shoulder tread and numerous tread blocks** with multiple grip edges.



Built on the **Conti 3G Casing** for maximum retreadability.

Superior casing construction allows high air dispersion for improved durability and enhanced retreadability.

Applications: Long haul, over the highway drive position.