

HDL Eco Plus

Fuel Efficient,
Long Haul Drive

Applications: Long haul, over the highway, drive position.





Legend:

3G Casing	SmartWay Verified	With TPMS Sensor	Retread Available
-----------	-------------------	------------------	-------------------

HDL Eco Plus

Fuel Efficient, Long Haul Drive

GOODS PEOPLE CONSTRUCTION



PRODUCT DATA



TIRE SIZE	LOAD RANGE	ARTICLE NUMBER	TREAD DEPTH (32nds)	MAX SPEED (MPH)	STATIC LOADED RADIUS		OVERALL INFLATED DIAMETER		OVERALL INFLATED WIDTH		LOADED SECTION WIDTH		APPROVED RIM(S)	MINIMUM DUAL SPACING		REVS PER UNIT		TIRE WEIGHT		MAX. LOAD @ INFLATION	
					IN	MM	IN	MM	IN	MM	IN	MM		IN	MM	MI	KM	LB	KG	SINGLE	DUAL
					LBS, PSI (KG, KPa)		LBS, PSI (KG, KPa)														
11R22.5*	G	05682990000	28	75	196	498	42.0	1066	11.1	282	12.1	307	8.25, 750	12.5	318	493	306	127	58	6175, 105 (2800, 720)	5840, 105 (2650, 720)
275/80R22.5*	G	05683980000	28	75	18.9	480	40.8	1036	11.0	279	12.1	307	8.25, 750	12.5	318	509	315	119	54	6175, 110 (2800, 760)	5675, 110 (2575, 760)
275/80R22.5*	H	05683770000	28	75	18.9	480	40.8	1036	11.0	279	12.1	307	8.25, 750	12.5	318	509	315	119	54	6940, 120 (3150, 830)	6175, 120 (2800, 830)
11R24.5*	H	05683760000	28	75	20.6	523	44.0	1117	11.1	282	12.1	307	8.25, 750	12.5	318	470	292	136	62	7160, 120 (3250, 830)	6610, 120 (3000, 830)
285/75R24.5*	H	05683780000	28	75	19.6	498	42.0	1066	10.7	272	12.1	307	8.25, 750	12.5	318	493	306	128	58	6780, 120 (3075, 830)	6175, 120 (2800, 830)

TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS

Note - Rim listed first is the measuring rim. Minimum Dual Spacing calculated without chains. * - ECE Certified. # - Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Tire the Americas, LLC. reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.



Advanced tread compound provides long original mileage and low rolling resistance.



Closed shoulder tread design provides even tread wear while still providing excellent traction.



Stone ejection system reduces stone retention and casing penetrations.



28/32" tread depth for optimized mileage and rolling resistance.

Applications: Long haul, over the highway, drive position.