

# HDR Regional Drive

Applications: Drive position, short and long haul. On/off highway service.



Legend:

3G Casing	SmartWay Verified	With TPMS Sensor	Retread Available
-----------	-------------------	------------------	-------------------

# HDR

## Regional Drive



GOODS PEOPLE CONSTRUCTION

### PRODUCT DATA



TIRE SIZE	LOAD RANGE	ARTICLE NUMBER	TREAD DEPTH (32nds)	MAX SPEED (MPH)	STATIC LOADED RADIUS		OVERALL INFLATED DIAMETER		OVERALL INFLATED WIDTH		LOADED SECTION WIDTH		APPROVED RIM(S)	MINIMUM DUAL SPACING		REVS PER UNIT		TIRE WEIGHT		MAX. LOAD @ INFLATION	
					IN	MM	IN	MM	IN	MM	IN	MM		IN	MM	MI	KM	LB	KG	SINGLE (LBS, PSI) (KG, KPa)	DUAL (LBS, PSI) (KG, KPa)
255/70R22.5*	H	05223330000	26	81	17.3	439	37.0	94.0	10.0	255	10.8	274	8.25, 750	11.3	287	559	347	97	44	5510, 120 (2500, 830)	5070, 120 (2300, 830)

TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS

Note - Rim listed first is the measuring rim. Minimum Dual Spacing calculated without chains. \* - ECE Certified. # - Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.



**Multi-service tread compound** for local and long haul service.



**Offset center tread blocks** provide excellent all weather traction.

**Tapered tread grooves** reduce stone retention for long casing life and multiple retreads.

**Applications:** Drive position, short and long haul. On/off highway service.