

# HDR2 Eco Plus

## Fuel Efficient, Regional Drive

Applications: Drive position, regional hauling on highway service.



Legend:

3G Casing	SmartWay Verified	With TPMS Sensor	Retread Available
-----------	-------------------	------------------	-------------------

# HDR2 Eco Plus

Fuel Efficient, Regional Drive

GOODS PEOPLE CONSTRUCTION



## PRODUCT DATA



TIRE SIZE	LOAD RANGE	ARTICLE NUMBER	TREAD DEPTH (32nds)	MAX SPEED (MPH)	STATIC LOADED RADIUS		OVERALL INFLATED DIAMETER		OVERALL INFLATED WIDTH		LOADED SECTION WIDTH		APPROVED RIM(S)	MINIMUM DUAL SPACING		REVS PER UNIT		TIRE WEIGHT		MAX. LOAD @ INFLATION	
					IN	MM	IN	MM	IN	MM	IN	MM		IN	MM	MI	KM	LB	KG	SINGLE	DUAL
					LBS, PSI (KG, KPa)		LBS, PSI (KG, KPa)														
11R22.5	G	05221540000	30	75	19.8	502	42.2	1071	11.6	295	13.0	330	8.25, 750	12.5	318	491	305	136	61	6175, 105 (2800, 720)	5840, 105 (2650, 720)
295/75R22.5	G	05220650000	30	75	19.0	482	40.7	1034	11.5	292	12.9	328	8.25, 900	12.5	318	509	316	128	58	6175, 110 (2800, 760)	5675, 110 (2575, 760)

TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS

Note - Rim listed first is the measuring rim. Minimum Dual Spacing calculated without chains. \* - ECE Certified # - Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. 315/80R22.5 tires used on 8.25" rims are restricted to a maximum of 7610 lbs at 120 psi. Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.



Advanced tread compounding provides this Eco Plus version with **20% less rolling resistance** than the HDR2.



**30/32" tread** is compounded for low rolling resistance with long tread life used on highway and regional roads.



**Open shoulder tread design** provides excellent wet/dry traction while resisting irregular wear.



Built on the **Conti 3G casing** for maximum retreadability.

**Applications:** Drive position, regional hauling on highway service.