

HDR 19.5" Regional Drive

Applications: Regional hauling and on/off road, drive position.



Legend:

3G Casing	SmartWay Verified	With TPMS Sensor	Retread Available

HDR

19.5" Regional Drive

GOODS PEOPLE CONSTRUCTION



PRODUCT DATA



TIRE SIZE	LOAD RANGE	ARTICLE NUMBER	TREAD DEPTH (32nds)	MAX SPEED (MPH)	STATIC LOADED RADIUS		OVERALL INFLATED DIAMETER		OVERALL INFLATED WIDTH		LOADED SECTION WIDTH		APPROVED RIM(S)	MINIMUM DUAL SPACING		REVS PER UNIT		TIRE WEIGHT		MAX. LOAD @ INFLATION	
					IN	MM	IN	MM	IN	MM	IN	MM		IN	MM	MI	KM	LB	KG	SINGLE	DUAL
					LBS, PSI (KG, KPa)		LBS, PSI (KG, KPa)														
225/70R19.5*	G	05221460000	18	87	15.0	381	32.0	813	8.6	218	9.4	239	600, 675	10.0	254	647	402	62	28	3970, 110 (1800, 760)	3750, 110 (1700, 760)

TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS

Note - Rim listed first is the measuring rim. Minimum Dual Spacing calculated without chains. * - ECE Certified # - Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.




Advanced tread compound delivers improved fuel efficiency, increased removal miles and improved resistance to cuts and tears.



18/32" tread pattern provides excellent traction and long mileage in regional and local service.



Aggressive tread design provides excellent lateral stability to minimize squirm and improve wet handling performance.



Open shoulder tread pattern with tie-bar provides even tread wear along with reduced noise and improved traction.

Applications: Regional hauling and on/off road, drive position.