

HTC1

Construction All-Position





⋖ GOODS ● PEOPLE **⋖** CONSTRUCTION

PRODUCT DATA








	LOAD RANGE	ARTICLE NUMBER	TREAD DEPTH (32nds)	MAX SPEED (MPH)	STATIC LOADED RADIUS		OVERALL INFLATED DIAMETER		OVERALL INFLATED WIDTH		LOADED SECTION WIDTH		APPROVED RIM(S)	MINIMUM DUAL SPACING		REVS PER UNIT		TIRE WEIGHT		MAX. LOAD @ INFLATION	
TIRE SIZE																				SINGLE	DUAL
					IN	ММ	IN	ММ	IN	ММ	IN	ММ	KIIVI(3)	IN	ММ	МІ	КМ	LB	KG	LBS, PSI (KG, KPa)	LBS, PSI (KG, KPa)
385/65R22.5 *	L	05350090000	22	68	19.5	495	42.0	1067	14.7	373	16.2	411	12.25, 11.75	N/A	N/A	493	306	167	76	9920, 130 (4500, 900)	N/A
425/65R22.5	L	05350100000	24	68	20.4	517	44.5	1130	16.6	422	18.0	457	12.25, 13.00, 14.00	N/A	N/A	465	289	183	83	11400, 120 (5150, 830)	N/A
445/65R22.5*	L	05350190000	22	68	20.9	530	45.2	1148	17.4	441	18.6	472	13.00, 14.00	N/A	N/A	462	287	210	95	12800, 120 (5800, 830)	N/A
						TUB	ELESS	TIRES (ON 15	DEGRE	E DRO	P CENT	ER RIMS								

Note - Rim listed first is the measuring rim. * - ECE Certified # - Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change 01 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Time the Americas, LLC reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.



Aggressive multi-service, **all-position tread pattern** provides excellent traction.

Outstanding **self-cleaning properties** ensure a long service life.



Cut and tear resistant tread compound for long tread life in on/off road conditions.



Rugged casing design resists casing penetrations and damage, allowing multiple retreads.

Applications: Wide base, all-position fitment for on/off, mixed service applications.