

HSR+ 19.5" Regional All-Position

Applications: Regional hauling and on/off road, all-position.



Legend:

| | | | |
|-----------|-------------------|------------------|-------------------|
| | | | |
| 3G Casing | SmartWay Verified | With TPMS Sensor | Retread Available |

HSR+

19.5" Regional All-Position

GOODS PEOPLE CONSTRUCTION




PRODUCT DATA



| TIRE SIZE | LOAD RANGE | ARTICLE NUMBER | TREAD DEPTH (32nds) | MAX SPEED (MPH) | STATIC LOADED RADIUS | | OVERALL INFLATED DIAMETER | | OVERALL INFLATED WIDTH | | LOADED SECTION WIDTH | | APPROVED RIM(S) | MINIMUM DUAL SPACING | | REVS PER UNIT | | TIRE WEIGHT | | MAX. LOAD @ INFLATION | |
|--------------|------------|----------------|---------------------|-----------------|----------------------|-----|---------------------------|-----|------------------------|-----|----------------------|-----|-----------------|----------------------|-----|---------------|-----|-------------|----|-----------------------|-----------------------|
| | | | | | IN | MM | IN | MM | IN | MM | IN | MM | | IN | MM | MI | KM | LB | KG | LBS, PSI (KG, KPa) | LBS, PSI (KG, KPa) |
| | | | | | | | | | | | | | | | | | | | | | |
| 225/70R19.5* | G | 05125520000 | 16 | 87 | 151 | 382 | 321 | 816 | 8.7 | 221 | 9.3 | 237 | 6.00, 6.75 | 10.0 | 254 | 644 | 400 | 63 | 29 | 3970, 110 (1800, 760) | 3750, 110 (1700, 760) |

TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS

Note - Rim listed first is the measuring rim. Minimum Dual Spacing calculated without chains. * - ECE Certified # - Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.



Improved cap/base tread compound for increased removal miles and resistance to tears.



Aggressive tread design provides excellent lateral stability to minimize squirm, and improve handling.



Closed shoulder tread pattern provides even wear and reduced noise.



Scuff rib to protect against curbing, cuts and abrasions.



Mileage Improvement vs. HSR

HSR+ delivers 13% improvement in removal miles vs. HSR.

Applications: Regional hauling and on/off road, all-position.