

Agricultural Tires VF TractorMaster

- › VF technology allows for driving with approx. 40% lower tire air pressure or approx. 40% higher load
- › D.fine lug technology ensuring high mileage
- › N.flex technology delivers robustness



Application

- › The right choice for flexibility for works that require frequent moves from road to field and field to road



VF Technology

More gripping edges in contact with soil for increased traction

Lower tire pressure and wider footprint reduce soil compaction



D.fine lug technology

5% more lug surface results in higher mileage compared to standard tires.

The overlap of lugs leads to a comfortable and smooth drive



VF Technology

Belt and bead geometry enhance sturdiness and durability

N.flex technology delivers flexibility for bead area and sidewall

Tire size LI/SSY	Rim Width	Section width (mm)	Overall diame- ter (mm)	Loaded static radius (mm)	Rolling circum- ference (mm)	Speed Radius Index	Tire load capacity (kg) at tire pressure (kPa)								Speed (km/h)				
Advanced tire							40	60	80	100	120	140	160	200	240				
30 Inch																			
VF 600/60R30 NRO 162D/159E Ⓢ	21	627*	1510*	660	4445	700				2830	3180	3525	3875	4375		70			
	20	617*								2720	3105	3485	3870	4250	4750		≤ 65		
	18	597*					1915	2340	2720	3105	3485	3870	4250	4750		≤ 30			
VF 600/70R30 NRO 168D/165E	21	633*	1636*	701	4772	750				3470	3895	4325	4750	5150		70			
	20	623*								3295	3760	4225	4685	5150	5600		≤ 65		
	18	603*					2320	2835	3295	3760	4225	4685	5150	5600		≤ 30			
42 Inch						40	60	80	100	120	140	160	200	240					
VF 710/60R42 NRO 176D/173E Ⓢ	27	763*	1953*	864	5782	925				4380	4920	5460	6000	6500		70			
	25	743*								4160	4745	5330	5915	6500	7100		≤ 65		
	24	733*								2925	3575	4160	4745	5330	5915	6500	7100		≤ 30
	23	723*											5185	5820	6460	7100	7750		70
VF 710/70R42 182D/179E	25	750*	2101*	912	6165	975				4960	5660	6355	7055	7750	8500		≤ 65		
	24	740*								3490	4265	4960	5660	6355	7055	7750	8500		≤ 30
	23	730*																	

* ETRTO max. values

Ⓢ Planned

Specifications are subject to change without notice.

For further technical information, see data sheets.

For details regarding product availability, please contact your local sales representative.