

ContiUrban HA3

Premium Tyre for **Urban** Applications
Engineered in Germany



We are offering a premium retread solution for our high-value casings

ContiUrban HA3



- Greater tread width for up to 20% higher mileage.
- High-value casing provides the best basis for premium retreadability.
- Higher casing wire density for better curbstone impact resistance.
- Wider tread ribs and high-density interlocking sipes ensure excellent cornering stability.
- Further enhanced wet braking performance ensures safety.



Applications:

Urban application
All axle on city buses


⊙ Recommended axle

Technical data and recommended tyre pressures

Article Number	Tyre Sizes	Tread Pattern	Load Speed Index ¹⁾	Ply Rating	TT TL ²⁾	Speed Index & refspeed (km/h)	Tread Depth	Overall Inflated Diameter (mm)	Overall Inflated Width (mm)	Recommended Rim (Inches)	Min Dual Spacing (mm)	Stat. Radius (mm)	Rolling Circumference (mm)	Recommended Buffing Radius (mm)	Recommended Tread Liner Width (mm)	Maximum Load @ Inflation ³⁾			
																Single		Dual	
																KG	PSI (BAR)	KG	PSI (BAR)
05140150000	315/60R 22.5	Conti Urban HA3	152/148J	16	TL	J100	13.5	968	315	9.00	344	442	2880	1300	280	7100	131 (9.0)	12600	131 (9.0)
05140300000	275/70R 22.5	Conti Urban HA3	150/145J	16	TL	J100	19.5	957	275	7.50	303	447	2920	900	240	6700	131 (9.0)	11600	131 (9.0)
05140380000	305/70R22.5	Conti Urban HA3	152/148K	20	TL	K110	20.1	1000	305	8.25	334	463	3050	700	255	7100	131 (9.0)	12600	131 (9.0)
05140460000	11R 22.5	Conti Urban HA3	148/145J	16	TL	J100	21.2	1046	279	8.25	314	489	3200	550	230	6300	123 (8.5)	11600	123 (8.5)

Technical data : "No Liability Assumed!" Data acc. to DIN 7805/4, Wdk-Guidelines 134/2, 142/2, 143/14, 143/25
¹⁾ Load Index single/twin tyres fitment and Speed Symbol ²⁾ TT = Tube Type, TL = Tubeless ³⁾ For tyres pressures of 8.0 bar and over, use valve slit cover plates

ContiTread is offered in ContiUrban HA3 treadliners for suitable Continental casings.



Article Number	mm	mm	mm
18208020000	215	17.5	3195
18208030000	230		3195
18208150000	240		3195
18208050000	250		2925
18208060000	260		3035

Continental Tyre PJ Malaysia Sdn. Bhd. (4296 K)
 3rd Floor, 2 Jalan Tandang, 46050 Petaling Jaya,
 Selangor, Malaysia.
 Tel +603 7787 88 88