



Radial

Tire				Rim	TSR	Tube and Valve		Flap	Tire dimensions(mm) Maximum in Service					Inflation Pressure		Tire Load capacity (kg) (ETRTO)						
									Standard Value (ETRTO)		Actual value					Other vehicles at max. speed (km/h)					Fork lift trucks max 25 km/h	
Size	Tread	PR	LI/Speed	Rim	TSR Art. No.	Tube	Valve	Flap	Section Width	Overall Diameter	Section Width (+-1%)	Overall Diameter (+-1%)	Static Radius (+-1%)	bar	kPa	Stationary	10	25	40	50	Load wheel	Steering wheel
8"																						
125/75 R 8	IC70	12	100 A5	3.00 D-8	0793002	15x4½-8 / 125/75-8	43D-60	85-8	129	399	120	386	176	10,0	1000	1210	1040	800	710	670	1040	800
5.00 R 8	IC70	10	111 A5	3.00 D-8	0793017	5.00-8	41.5G-70	85-8	139	476	132	461	209	10,0	1000	1650	1420	1090	970	920	1420	1090
150/75 R 8	IC70	16	113 A5	4.33 R-8	0793003	16x6-8 / 18x7-8	41.5G70 / 60D	115-8	160	439	150	425	193	10,0	1000	1740	1495	1150	1025	970	1495	1150
180/70 R 8	ContiRT20	16	125 A5	4.33 R-8	0793003	16x6-8 / 18x7-8	41.5G70 / 60D	115-8	183	465	173	461	205	10,0	1000	2495	2145	1650	1470	-	2145	1650
180/70 R 8	ContiRV20	16	125 A5	4.33 R-8	0793003	16x6-8 / 18x7-8	41.5G70 / 60D	115-8	183	465	171	464	208	10,0	1000	2495	2145	1650	1470	1390	2145	1650
9"																						
6.00 R 9	ContiRT20	12	121 A5	4.00 E-9	0793004	6.00-9 / 21x8-9	41.5G70 / 60D	100-9	168	551	162	539	248	10,0	1000	2190	1885	1450	1245	-	1885	1450
6.00 R 9	ContiRV20	12	121 A5	4.00 E-9	0793004	6.00-9 / 21x8-9	41.5G70 / 60D	100-9	168	551	163	532	244	10,0	1000	2190	1885	1450	1290	1220	1885	1450
10"																						
6.50 R 10	ContiRT20	14	128A5	5.00 F-10	0793005	6.50/7.50-10	41.5G70 / 60D	130-10	186	600	181	590	272	10,0	1000	2720	2340	1800	1605	-	2340	1800
6.50 R 10	ContiRV20	14	128 A5	5.00 F-10	0793005	6.50/7.50-10	41.5G70 / 60D	130-10	186	600	183	586	269	10,0	1000	2720	2340	1800	1600	1515	2340	1800
225/75 R 10	ContiRT20	20	142 A5	6.50 F-10	0793007	23x9-10 / 225/75-10	60D / 75D	180-10	239	606	221	592	266	10,0	1000	4005	3445	2650	2360	-	3445	2650
225/75 R 10	ContiRV20	20	142 A5	6.50 F-10	0793007	23x9-10 / 225/75-10	60D / 75D	180-10	239	606	226	586	261	10,0	1000	4005	3445	2650	2360	2230	3445	2650
12"																						
7.00 R 12	ContiRT20	16	136 A5	5.00 S-12	0793001	7.00-12	60D / 75D	130-12	202	685	192	675	311	10,0	1000	3385	2915	2240	1995	1885	2915	2240
7.00 R 12	ContiRV20	16	136 A5	5.00 S-12	0793001	7.00-12	60D / 75D	130-12	202	685	194	669	307	10,0	1000	3385	2915	2240	1995	1885	2915	2240
250/75 R 12	ContiRT20	20	152 A5	8.00 G-12	0793011	27x10-12 / 250/75-12	60D / 75D	220-12	274	697	261	686	310	10,0	1000	5365	4615	3550	3160	-	4615	3550
13"																						
165 R 13	ContiRV20	-	102 A6	4.50 x 13 B	-	-	-	-	174	606	167	598	280	4,5	450	-	-	850	-	-	-	-
15"																						
7.00 R 15	ContiRV20	14	143 A5	5.5 -15	0793006	7.00-15 / 200-15	75D-74	170-15 reinforced	207	761	201	731	337	10,0	1000	4115	3540	2725	2425	2290	3540	2725
7.50 R 15	ContiRV20	16	146 A5	6.0 - 15	0793008	7.50-15 / 8.25-15	75D-74 / 95D-74	170-15 reinforced	223	787	219	770	353	10,0	1000	4530	3900	3000	2670	2520	3900	3000
8.25 R 15	ConRad HT1	18	153 A5	6.5 - 15	0793000	7.50-15 / 8.25-15	75D-74 / 105D	170-15 reinforced	246	853	238	842	388	10,0	1000	5515	4745	3650	3250	-	4745	3650
8.25 R 15	ContiRT20	18	153 A5	6.5 - 15	0793000	7.50-15 / 8.25-15	75D-74 / 105D	170-15 reinforced	246	853	237	834	381	10,0	1000	5515	4745	3650	3250	-	4745	3650
8.25 R 15	ContiRV20	18	153 A5	6.5 - 15	0793000	7.50-15 / 8.25-15	75D-74 / 105D	170-15 reinforced	246	853	238	842	385	10,0	1000	5515	4745	3650	3250	-	4745	3650
225/75 R 15	ContiRT20	16	149 A5	7.0 - 15	0793009	28x9-15 / 250/70-15	75D-74 / 95D-74	190-15 reinforced	245	733	222	721	330	10,0	1000	4910	4225	3250	2895	-	4225	3250
250/70 R 15	ContiRT20	18	153 A5	7.0 - 15	0793015	28x9-15 / 250/70-15	75D-74 / 95D-74	190-15 reinforced	264	745	242	740	338	10,0	1000	5515	4750	3650	3250	-	4745	3650
250/70 R 15	ContiRV20	18	153 A5	7.0 - 15	0793015	28x9-15 / 250/70-15	75D-74 / 95D-74	190-15 reinforced	264	745	240	743	338	10,0	1000	5515	4745	3650	3250	-	4745	3650
315/70 R 15	ContiRT20	22	165 A5	8.0 - 15	0793012	300-15 / 355/65-15	95D-74 / 95D-Z	240-15 reinforced	323	841	313	836	374	10,0	1000	7780	6695	5150	4585	-	6695	5150
315/70 R 15	ContiRV20	22	165 A5	8.0 - 15	0793012	300-15 / 355/65-15	95D-74 / 95D-Z	240-15 reinforced	323	841	304	830	368	10,0	1000	7780	6695	5150	4585	-	6695	5150
355/65 R 15	ContiRT20	-	170 A5	9.75 - 15	in preparation	300-15 / 355/65-15	95D-74 / 95D-Z	240-15 reinforced	373	861	336	839	366	10,0	1000	9060	7800	6000	-	-	7800	6000
20"																						
10.00 R 20	ContiRT20	18	166 A5	7.5 - 20	0793010	10.00-20	127D-Z	190-20 reinforced	297	1073	289	1069	495	10,0	1000	8000	6890	5300	4715	-	6890	5300
12.00 R 20	ConRad HT1	20	176 A5	8.5 - 20	0793010	11.00/12.00-20	127D-Z	230-20 reinforced	338	1144	311	1140	518	10,0	1000	10720	9230	7100	6320	-	9230	7100
12.00 R 20	ContiRT20	20	176 A5	8.5 - 20	0793010	11.00 / 12.00-20	127D-Z	230-20 reinforced	338	1144	308	1143	522	10,0	1000	10720	9230	7100	6320	-	9230	7100
12.00 R 20	ContiRV20	20	176 A5	8.5 - 20	7930100	11.00/12.00-20	127D-Z	230-20 reinforced	338	1144	311	1140	515	10,0	1000	10720	9230	7100	6320	-	9230	7100