

Continental 
The Future in Motion



Continental Racing Tires:

For ultimate performance
in racing applications.

ContiTrack

Slick tire for track days and hobby racers (NHS).

- › Sustainable performance together with higher durability.
- › New carcass construction for significantly greater braking stability, precise turn-in and noticeably better corner exit traction.
- › Compound variations, adapted to supersport bikes and superbikes.



ZeroDegree



Handmade in Germany

Rim Ø	Size	TL/TT	Compound	Article No.	Remarks
Front wheel 17"	120/70 R 17 NHS	TL	Soft	02 44 403	
	120/70 R 17 NHS	TL	Medium	02 44 404	
Rear wheel 17"	180/60 R 17 NHS	TL	Soft	02 44 410	
	180/60 R 17 NHS	TL	Medium	02 44 411	
	200/55 R 17 NHS	TL	Soft	02 44 631	
	200/55 R 17 NHS	TL	Medium	02 44 629	

Applications:

180/60 R 17	5 ½" Rims	for supersport bikes
200/55 R 17	6" Rims	for supersport bikes and superbikes

Compound variations:

Soft	Sprint racing, one-day training; good for high outdoor temperatures
Medium	Sprint racing, long-distance racing, 1-2 day training; for a wide range of outdoor temperatures

Recommendation:

Front wheel	Soft
Rear wheel	Medium




Recommended tire pressure:

For racing use: After at least an hour with the tire warmers at 176 °F / 80 °C, the tire pressure should be measured and adjusted immediately after the first short session.

ContiTrack	Front	Rear
Hot (80 °C / 176 °F)	2.25 bar / 32.5 psi	1.55 bar - 1.7 bar 22.5 psi - 24.6 psi

Rear wheel dimensions

Size	Diameter	Circumference	Width
180/60 R 17	649 mm	2039 mm	184 mm
200/55 R 17	655 mm	2058 mm	192 mm



ContiRace **ATTACK** Rain

Competition rain tire (NHS).

- › Innovative pattern design to ensure optimal water clearance and high grip in extreme wet track conditions.
- › Controllable ride with high feedback characteristics providing excellent traction even under hard riding conditions due to a state-of-the-art racing rain compound.



ZeroDegree



Handmade in Germany

Rim Ø	Size	TL/TT	Article No.	Remarks
Front wheel 17"	120/70 R 17 NHS	TL	02 44 263	
	180/55 R 17 NHS	TL	02 44 264	
Rear wheel 17"	180/55 R 17 NHS	TL	02 44 107	

Recommended tire pressure:

Tip: Use the tire without the tire warmer so that the rider can get used to the increasing grip. However, it is also possible to pre-heat the tire.
WARNING! Tire pressure depends on the outdoor temperature.

Use without tire warmers:

ContiRaceAttack Rain	Front	Rear
Cold	2.1 - 2.3 bar / 30.45 - 33.35 psi	2.1 - 2.3 bar

Use with tire warmers:

ContiRaceAttack Rain	Front	Rear
Hot (40 °C / 104 °F)	max. 2.4 bar / 34.80 psi	max. 2.4 bar / 34.80 psi

ContiRace **ATTACK** 2 soft / medium

DOT homologated race tire with BlackChili Compound for maximum performance lap after lap.

- › **PERFORMANCE:**
treaded race track tire for amateur racers.
- › **BLACKCHILI RACE-COMPOUND:**
for fast warm-up and consistently high grip - available in both soft and medium compound.
- › **CONSTRUCTION:**
higher stability when braking into and accelerating out of corners, together with constantly good feedback (GripLimitFeedback Technology).
- › **UNCOMPLICATED:**
simple application: in varying conditions these race tires maintain temperature more consistently.
- › **RACETRACKS:**
tested with lowered air pressure for race track use; tire warmers recommended for track use.



Street legal use up to 270 km/h (169 mph).

- › Depending on the application, it can be combined with the ContiRaceAttack 2 Street for longer durability needs at Endurance racing.



MultiGrip



ZeroDegree



GripLimitFeedback



Handmade in Germany

Rim Ø	Size	L/SI	TL/TT	Compound	Article No.	Remarks
Front wheel 17"	120/70 ZR 17 M/C	58 W	TL	Soft	02 44 650	NEW
	120/70 ZR 17 M/C	58 W	TL	Medium	02 44 654	NEW
Rear wheel 17"	160/60 ZR 17 M/C	69 W	TL	Soft	02 44 651	NEW
	160/60 ZR 17 M/C	69 W	TL	Medium	02 44 655	NEW
	180/60 ZR 17 M/C	75 W	TL	Soft	02 44 652	NEW
	180/60 ZR 17 M/C	75 W	TL	Medium	02 44 656	NEW
	190/55 ZR 17 M/C	75 W	TL	Soft	02 44 653	NEW
	190/55 ZR 17 M/C	75 W	TL	Medium	02 44 657	NEW

Recommended tire pressure:

For racing use: After at least an hour with the tire warmers at 176 °F / 80 °C, the tire pressure should be measured and adjusted immediately after the first short session.

ContiRaceAttack 2 soft / medium	Front	Rear
Cold	2.2 - 2.3 bar / 31.90 - 33.35 psi	2.0 bar / 29.00 psi
Hot (80 °C / 176 °F)	2.4 - 2.5 bar / 34.80 - 36.25 psi	up to 2.4 bar / 34.80 psi


ContiRace *ATTACK* 2 Street

Our fastest Hypersport tire with BlackChili Performance from the race track to the road.

- › **PERFORMANCE:**
our race track tire - also for your favourite road rides.
- › **BLACKCHILI HYPERSPORT-COMPOUND:**
for maximum grip on road and racetrack surfaces.
- › **PROFILE:**
minimal negative tread, no grooves on shoulder to allow maximum grip at lean angles.
- › **TRUST:**
maximum predictability at the limit due to special carcass construction and tread compound (GripLimitFeedback Technology).
- › **RACETRACKS:**
tested with lowered air pressure for race track use; also suitable for tire warmers.



For even greater performance on the racetrack the ContiRaceAttack 2 Street may be combined with the ContiRaceAttack 2 soft / medium.



Rim Ø	Size	LI/SI	TL/TT	Article No.	Remarks
Front wheel					
17"	120/70 ZR 17 M/C	(58 W)	TL	02 44 658	NEW
Rear wheel					
17"	180/55 ZR 17 M/C	(73 W)	TL	02 44 659	NEW
	190/50 ZR 17 M/C	(73 W)	TL	02 44 660	NEW
	190/55 ZR 17 M/C	(75 W)	TL	02 44 661	NEW
	200/55 ZR 17 M/C	(78 W)	TL	02 44 662	NEW

Recommended tire pressure:


For racing use: After at least an hour with the tire warmers at 176 °F / 80 °C, the tire pressure should be measured and adjusted immediately after the first short session.

ContiRaceAttack 2 Street	Front	Rear
Cold	2.2 - 2.3 bar / 31.90 - 33.35 psi	2.0 bar / 29.00 psi
Hot (80 °C / 176 °F)	2.4 - 2.5 bar / 34.80 - 36.25 psi	up to 2.4 bar / 34.80 psi

ContiSport *ATTACK* 4

Maximum grip with BlackChili Performance, accuracy and easy handling for the most powerful superbikes.

- › **BLACKCHILI SPORT-COMPOUND:**
more grip and improved traction thanks to the latest compound technology.
- › **NEW PROFILE DESIGN:**
larger footprint at extreme lean angles.
- › **HANDLING:**
typical Conti agility and precision when turning.
- › **WARM-UP:**
rapid warm-up for confidence from the first kilometres.
- › **WET HANDLING:**
RainGrip technology of the Continental test winners.
- › **TRACK DAYS:**
also suitable for hobby race track use (without tire warmers).



Rim Ø	Size	LI/SI	TL/TT	Article No.	Remarks
Front wheel					
17"	120/60 ZR 17 M/C	(55 W)	TL	02 44 597	NEW
	120/70 ZR 17 M/C	(58 W)	TL	02 44 598	NEW
	120/70 ZR 17 M/C	(58 W)	TL C	02 44 684	NEW
Rear wheel					
17"	160/60 ZR 17 M/C	(69 W)	TL	02 44 604	NEW
	180/55 ZR 17 M/C	(73 W)	TL	02 44 603	NEW
	190/50 ZR 17 M/C	(73 W)	TL	02 44 602	NEW
	190/50 ZR 17 M/C	(73 W)	TL C	02 44 685	NEW
	190/55 ZR 17 M/C	(75 W)	TL	02 44 600	NEW
	190/55 ZR 17 M/C	(75 W)	TL C	02 44 686	NEW
	200/55 ZR 17 M/C	(78 W)	TL	02 44 599	NEW

C = Is primarily used on BMW models

ContiRoad **ATTACK** 3 CR

Perfect choice for heavy, powerful
Classic Sport- and Superbikes.

- › Successor of the legendary and well reputed test winner ContiRoadAttack 2 CR.
- › Optimized racing compound for maximum grip.
- › Special radial classic bike carcass for narrow rims providing extraordinary handling and stability; the Benchmark in the Classic Racing Segment.
- › Improved wet performance due to a new tread pattern design and compound, developed for Classic and Vintage racing.
- › Customized pattern design for the size 150/65 R 18 for maximum performance under acceleration at corner exit.
- › GripLimitFeedback for predictable handling at the limit.



150/65 R 18



TractionSkin



MultiGrip



ZeroDegree



RainGrip



GripLimitFeedback



Handmade
in Germany

Rim Ø	Size	LI/SI	TL/TT	Standard rims (ETRTO)	Article No.	Remarks
Front wheel						
18"	100/90 R 18 M/C	56 V	TL	1.60 x 18 1.85 x 18 2.15 x 18 2.50 x 18 2.75 x 18	02 44 564	
	110/80 ZR 18 M/C	(58 W)	TL	2.15 x 18 2.50 x 18 2.75 x 18 3.00 x 18	02 44 565	
Rear wheel						
18"	110/80 R 18 M/C	58 V	TL	2.15 x 18 2.50 x 18 2.75 x 18 3.00 x 18	02 44 583	
	130/80 R 18 M/C	66 V	TL C	2.75 x 18 3.00 x 18 3.50 x 18	02 44 566	
	150/65 R 18 M/C	69 H	TL	4.00 x 18 4.25 x 18 4.50 x 18	02 44 558	

C = Reinforced carcass

Rim classifications

Front wheel

Size	Standard rim (ETRTO)
100/90 R 18 M/C 56V TL	1.85 x 18; 2.50 x 18; 2.75 x 18
110/80 ZR 18 M/C (58W) TL	2.50 x 18; 2.75 x 18; 3.00 x 18

Rear wheel

Size	Standard rim (ETRTO)
110/80 R 18 M/C 58 V TL	2.15 x 18; 2.50 x 18; 2.75 x 18; 3.00 x 18
130/80 R 18 M/C 66V TL	3.00 x 18; 3.50 x 18
150/65 R 18 M/C 69H TL	4.00 x 18; 4.25 x 18; 4.50 x 18


Recommended tire pressure:

ContiRoadAttack 3 CR	Front	Rear
Cold	100er - 2.1 - 2.2 bar / 30.45 - 31.9 psi 110er - 2.2 - 2.3 bar / 31.9 - 33.35 psi	130er - 2.0 - 2.2 bar / 29 - 31.9 psi 150er - 1.8 - 2.0 bar / 26.1 - 29 psi
















When should I use each tire?

The tire temperature should be measured immediately after the first lap and tire pressure should be adjusted.

Temperature
in °C / °F



- ContiTrack:**
For track racing and race training. Use of tire warmers recommended. NHS - Not street legal.
- ContiRaceAttack 2 soft / medium:**
For track racing and race training. Use of tire warmers recommended. Street legal up to 270 km/h / 169 mph.
- ContiRaceAttack 2 Street:**
For riding and race training in dry conditions. Use without tire warmers possible. Street legal.
- ContiSportAttack 4:**
Also suitable for hobby race track use (without tire warmers).
- ContiRaceAttack Rain:**
For use on completely wet race tracks. NHS - Not street legal.
- ContiRoadAttack 3 CR:**
18" racing tire for use on classic motorcycles. Street legal.

ContiRaceAttack 2 soft / medium	ContiRaceAttack 2 Street	ContiSportAttack 4
Racing	Hypersport	Supersport
 90%	 50%	 10%
 10% (≤ 270 km/h)	 50%	 90%
Reduced tire pressure for the race track 	Reduced tire pressure for the race track 	Reduced tire pressure for the race track 
Can be combined with ContiRaceAttack 2 Street 	Can be combined with ContiRaceAttack 2 soft / medium 	
Tire warmer (recommended) 	Tire warmer (possible) 	Tire warmer (no) 

Continental Reifen Deutschland GmbH

Business Unit Motorcycle Tires
Continentalstraße 3 - 5
34497 Korbach
Germany




Postfach 11 20
34481 Korbach
Germany

Phone: +49.511 9 38 - 01
Fax: +49.5631 58 - 22 40
E-Mail: service.motorrad@conti.de
Internet: www.conti-moto.com

Legal Notice:

Continental Reifen Deutschland GmbH accepts no liability in conjunction with this publication. To the extent permitted by law, any liability for any direct, indirect, incidental, consequential or punitive damages of any kind arising out of the use of the information included in this publication is hereby excluded.

Your local dealer.



Further information can be obtained from
www.conti-moto.com